
bookboon.com
https://answersun.com/download/solutions-manual-of-engineering-thermodynamics-by-shemmeri-1st-edition/

Engineering Thermodynamics Solutions Manual

Prof. T.T. Al-Shemmeri



Download free books at
bookboon.com
Download full file from answersun.com

https://answersun.com/download/solutions-manual-of-engineering-thermodynamics-by-shemmeri-1st-edition/

Prof. T.T. Al-Shemmeri

Engineering Thermodynamics Solutions Manual

Download free eBooks at bookboon.com

Download full file from answersun.com

https://answersun.com/download/solutions-manual-of-engineering-thermodynamics-by-shemmeri-1st-edition/

Engineering Thermodynamics Solutions Manual
© 2012 Prof. T.T. Al-Shemmeri & bookboon.com
ISBN 978-87-403-0267-7


Download free eBooks at bookboon.com

Download full file from answersun.com

https://answersun.com/download/solutions-manual-of-engineering-thermodynamics-by-shemmeri-1st-edition/

Contents

	Foreword	**5**
4.1	**First Law of Thermodynamics N.F.E.E Applications**	**6**
4.2	**First Law of Thermodynamics S.F.E.E Applications**	**10**
4.3	**General Thermodynamics Systems**	**16**



Download free eBooks at bookboon.com

Click on the ad to read more

Download full file from answersun.com

https://answersun.com/download/solutions-manual-of-engineering-thermodynamics-by-shemmeri-1st-edition/

4.2 First Law of Thermodynamics S.F.E.E Applications

1. A boiler is designed to work at 14 bar and evaporate 8 kg/s of water. The inlet water to the boiler has a temperature of 40 deg C and at exit the steam is 0.95 dry. The flow velocity at inlet is 10 m/s and at exit 5 m/s and the exit is 5 m above the elevation at entrance. Determine the quantity of heat required. What is the significance of changes in kinetic and potential energy on the result?

[Ans: 20.186 MW]

Solution:

1. SFEE : $Q - W = m[(h_2 - h_1) + \frac{V_2^2 - V_1^2}{2} + g(z_2 - z_1)]$

W =0 (since constant pressure process),

ignoring Δke and ΔPe: the SFEE reduces to

$Qs = m_s (h_2 - h_1)$

State 1- h_1 is hf at T=40C, closest to this is Ts=45, h1=191.83 kJ/kg

State 2, $h=h_f+0.95h_{fg}$ at 14 bar.

h_2=830.30+0.95x1959.7 = 2692 kJ/kg

hence

$Qs= m_s (h_2 - h_1)$= 8 x(2692 – 191.83) = 2000136 kW= 20 MW

2. Taking into account changes in KE and PE

The KE and PE contribution is calculated

$$X = m[\frac{V_2^2 - V_1^2}{2}] + g(Z_2 - Z_1)]$$

$$= 8x[\frac{5^2 - 10^2}{2000} + 9.81x(\frac{5}{1000})]$$
$$= -0.3 + 0.049$$
$$= -0.251\,kW$$

This is tiny (0.001%) in comparison to 20 MW.

Download free eBooks at bookboon.com

Download full file from answersun.com