

Solutions Manual

to accompany

Unit Operations of Chemical Engineering

Seventh Edition

Prepared by
Julian C. Smith
Peter Harriott

PROPRIETARY AND CONFIDENTIAL

This Manual is the proprietary property of The McGraw-Hill Companies, Inc. ("McGraw-Hill") and protected by copyright and other state and federal laws. By opening and using this Manual the user agrees to the following restrictions, and if the recipient does not agree to these restrictions, the Manual should be promptly returned unopened to McGraw-Hill: **This Manual is being provided only to authorized professors and instructors for use in preparing for the classes using the affiliated textbook. No other use or distribution of this Manual is permitted. This Manual may not be sold and may not be distributed to or used by any student or other third party. No part of this Manual may be reproduced, displayed or distributed in any form or by any means, electronic or otherwise, without the prior written permission of McGraw-Hill.**

PROPRIETARY MATERIAL. © The McGraw-Hill Companies, Inc. All rights reserved. No part of this Manual may be displayed, reproduced or distributed in any form or by any means, without the prior written permission of the publisher, or used beyond the limited distribution to teachers and educators permitted by McGraw-Hill for their individual course preparation. If you are a student using this Manual, you are using it without permission.

Chapter 2

2-1. Use Eq. (2-10) noting that

$1 \text{ g/cm}^3 = 1000 \text{ kg/m}^3$. Quantities needed are:

$g = 9.80665 \text{ m/s}^2$ (Eq. (1-13)) $R_m = 0.2 \text{ m}$

$$\begin{aligned} P_a - P_b &= 9.80665 \times 0.2 (13.6 - 1.6) 1000 \\ &= 23536 \text{ kg} \cdot \text{m/m}^2 \cdot \text{s}^2 = 23536 \text{ N/m}^2 \end{aligned}$$

2-2. Find a relation between temperature and elevation.

From the given conditions:

$$\frac{dT}{dz} = - \frac{5}{1000} = -0.005$$

Integrating between limits, setting $T = 288\text{K}$ at $Z = 0$ gives

$$T = 288 - 0.005Z$$


Substituting for T in Eq. (2-6) and integrating gives

$$\int_{P_a}^{P_b} \frac{dp}{P} = - \frac{gM}{R} \int_{Z_a}^{Z_b} \frac{dz}{288 - 0.005Z}$$

Since $Z_a = 0$

$$\ln \frac{P_a}{P_b} = \frac{gM}{0.005R} \ln \frac{288}{288 - 0.005Z_b}$$

13.3



Assume orientation
of tubes as shown

Maximum capacity of condenser will be based on a very large flow of cooling water, so h_i is infinite and the exit water temperature is 70°F .

$$D_o = 1.5/12 = 0.125 \text{ ft}$$

$$\bar{D}_L = 1/12[(1.5 - 1.3)/(\ln 1.5/1.3)] = 0.1165 \text{ ft}$$

Resistance of metal wall:

$$\frac{x_w D_o}{k_m D_L} = \frac{0.1 \times 0.125}{12 \times 26 \times 0.1165} = 0.00034$$

Estimate surface temperature T_{w0} to be 73°F (found by trial). $T_o = 82 - 73 = 9^\circ\text{F}$

$$T_f = 82 - (0.75 \times 9) = 75.3^\circ\text{F}$$

$$\mu_f = 0.11 \times 2.42 = 0.266 \text{ lb/ft-h (Appendix 9)}$$

$$k_f = 0.29 \text{ Btu/h-f-}^\circ\text{F (Appendix 13)}$$

$$\rho_f = (1/0.00165)/16.0185 = 37.84 \text{ lb/ft}$$

$$(\text{Perry, 7}^{\text{th}} \text{ ed., p. 2-214})$$

$$\lambda = 500 \text{ Btu/lb}$$

From Eq. (13.17), for each stack of tubes,

27.5. From Eq. (27.23) the growth rate is

$$G = B^0/n^0 = 1.84/1.46 \times 10^6$$

$$= 1.26 \times 10^{-6} \text{ cm/s or } 0.0454 \text{ mm/h}$$

From Eq. (27.25) , since $B^0/n^0 G = 1$,

$$K_N = \frac{t_{To}}{u_T^2 \rho_c (G\tau)^5}$$

$$= \frac{35}{1350^2 \times 2.163 \times (0.0454 \times 1.80)^5}$$

$$= 2.436$$

27.6. (a) Assume $Sh = 2.0$ or $k_c = 2D_v/D_p$

The rate of change of mass is:

$$\frac{d(\rho_s \pi D_p^3 / 6)}{dt} = -\pi D_p^2 k_c \Delta C$$

$$3\rho_s D_p^2 dD_p / 6 = - D_p^2 (2D_v / D_p) \Delta C$$

$$\int D_p dD_p = - \int \frac{4D_v \Delta C}{\rho_s} dt$$

$$D_p^2 / 2 = - 4D_v \Delta C t / \rho_s$$

For complete dissolution

$$- \Delta D_p^2 = D_p^2 = 8D_v \Delta C t / \rho_s$$

$$\rho_s = 1.988 \text{ g/cm}^3$$

Use Eq. (17.24) and Table 17.1 with λ for K^+ and Cl^- . For dilute solutions at $25^\circ C$,

$$D_v = \frac{2 \times 8.314 \times 298}{(1/73.5 + 1/76.3)96,500^2}$$

$$= 1.99 \times 10^{-5} \text{ cm}^2/\text{s}$$

Correct to $130^\circ F$ or $54.4^\circ C$, using T/μ ratios for water (see Appendix 6):

At 20°C, $\bar{V} = 0.265 (293/273) = 0.284 \text{ m/s}$

$\mu = 0.018 \text{ cP} = 1.8 \times 10^{-5} \text{ Pa.s}; \rho = 1.206 \text{ kg/m}^3$

$$\text{Re} = \frac{300 \times 10^{-6} \times 0.284 \times 1.206}{1.8 \times 10^{-5}} = 5.71$$

Use Eq. (5.20) for laminar flow, in differential form,

$$\frac{dP}{dL} = \frac{32\bar{V}\mu}{D^2}$$

Assume a constant permeation rate over the fiber length.

$$\bar{V} = \bar{V}_{\text{exit}} \frac{L}{L_T}$$

$$dP = \frac{32\bar{V}_{\text{exit}}\mu L}{D^2 L_T} dL$$

By integration, $\Delta P = \frac{32\bar{V}_{\text{exit}}\mu L_T^2}{2D^2 L_T}$

For $L_T = 1$, $\Delta P = \frac{16 \times 0.284 \times 1.8 \times 10^{-5}}{(300 \times 10^{-6})^2} = 909 \text{ Pa} = 9.09 \times 10^{-3} \text{ bar}$

(b) For 150- x 300- μm fibers, the permeate flux per fiber would be half as great, but the cross-sectional area is reduced by four, so \bar{V} is two times greater. ΔP depends on \bar{V}/D^2 . So ΔP changes to:

$$909 \times 2 \times 4 = 7270 \text{ Pa} = 0.073 \text{ bar.}$$

26.12(a) $R = 0.05 = P_1/P_2$ Let $P_1 = 20 \text{ atm}$, $P_2 = 1 \text{ atm}$

Basis: $F = 100$, $x_F = 0.01$, $y = 0.049$. Stage cut = 19 percent

$$V = 0.19F, F = 19, L = F - V = 81$$

Check CFC balance. In: $100 (0.01) = 1$

$$\text{Out: } 19 (0.049) + 81 (0.001) = 1.012. \text{ OK.}$$

For CFC at inlet end, $p_{1, \text{CFC}} = 20 (0.01) = 0.2 \text{ atm}$

$$p_{2, \text{CFC}} = 1 (0.049) = 0.049 \text{ atm}$$

$$\Delta p_{\text{CFC}} = 0.2 - 0.049 = 0.151 \text{ atm}$$

At the residue end, $p_{1, \text{CFC}} = 20 (0.001) = 0.02 \text{ atm}$

In 10 seconds, transfer $10 \times \frac{9.12 \times 10^{-10}}{4.36 \times 10^{-8}} \times 100 = 21\%$ of O_2 in bubble

If P is the same, the bubble size is reduced to $1 \times (0.79)^{1/3} = 0.92$ mm.

However, in 10 seconds the bubble might rise 120 cm or 4 ft and P would be $\left(\frac{30}{34}\right)^{1/3} + 1 = 1.88$ atm. The corrected bubble size is $(0.79 \times 2/1.88)^{1/3} \times 1 = 0.94$ mm.

A numerical solution would be needed to allow for the change in bubble size, area, oxygen concentration and mass transfer coefficient as the bubble rises in a quiescent liquid. In a stirred tank, small bubbles could be carried downward in some regions and have more time to dissolve.

The bubble rise velocity is reduced to $\sim 0.92(12) = 11$ cm/s, but the mass transfer coefficient is almost the same.

$$Re = \frac{0.092(11)1.0}{0.01} = 101$$

$$Sh = 49.9$$

$$k_c = 0.0106 \text{ cm/s}$$

When 90% of the O_2 has been absorbed,

$$D = 1.0(0.1)^{1/3} = 0.464 \text{ mm}, \quad u_r \cong 5.6 \text{ cm/s}$$

$$Re = \frac{0.0464(56)1}{0.01} = 26.0$$

$$Sh = 26.3$$

$$k_c = 0.0113 \text{ cm/s}$$